


MEDIUS LED

WALL DIRECT/INDIRECT
ASYMMETRIC



LUMENWERX
WWW.LUMENWERX.COM



Shown with HLO optics

DESCRIPTION

Within its compact 115/16" x 4 3/4" profile, Medius supports optics for high performance direct/indirect lighting. The result is efficacy up to 115 LPW. Medius configures as individual luminaires or continuous runs and features the full range of electrical and control options.

PROJECT: _____

TYPE: _____

NOTES: _____

ORDER GUIDE

up to 115 lm/w performance


MEDWDI	HLO	WAI	LED		
LUMINAIRE ID	DIRECT OPTICS	INDIRECT OPTICS	LIGHT SOURCE	CRI	DIRECT LUMEN PACKAGES
MEDWDI - Medius wall direct/indirect	HLO - High-Efficiency Lambertian Optic	WAI - widespread asymmetric indirect optics	LED - high performance LED	80 - 80CRI 90 - 90CRI	350 - min. eco low output 350lm/ft 500 - low output 500lm/ft 750 - medium output 750lm/ft 1000 - max. high output 1000lm/ft #### - other required lm/ft

INDIRECT LUMEN PACKAGES	COLOR TEMP.	LUMINAIRE LENGTH	VOLTAGE	DRIVER
500 - min. low output 500lm/ft 750 - medium output 750lm/ft #### - other required lm/ft	27 - 2700k 30 - 3000k 35 - 3500k 40 - 4000k	Standard sections - 4', 8' & 12' For all other specify length #FT - nominal length in feet only Continuous Run - for luminaires over 12' Minimum Individual section 4'	120 - 120V 277 - 277V UNV - 120V-277V 347 - 347V (not available with Lutron)	D1 - 1% dimming 0-10V DA - Dali LTEA2W - Lutron 1% - 2 wire FF 120V LDE1 - Lutron Hi-lume 1% Eco LDE5 - Lutron 5% EcoSystem

ELECTRICAL	DMB	FINISH	CONTROLS	OPTIONS
	MOUNTING			
1 - 1 circuit 2 - 2 circuits + #EB - emergency battery (min 8' fixture, except Lutron) + #EM - emergency light circuit + #NL - night light circuit	DMB - drywall mounting bracket	W - matte white AL - aluminum CF# - custom finish specify RAL#	<u>STANDALONE CONTROLS</u> OMS - Onboard Occupancy ODS - Onboard Daylight OCS - Onboard Occupancy & Daylight <u>CONNECTED CONTROLS</u> CCS() - LU-Lutron, EN-Enlighted, OS-Osram, CR-Crestron. To specify see information on page 3	FU - fuse TB# - T-bar caddy clip specify grid size TG# - Tegular caddy clip specify grid size ST - Screw Slots caddy clip CU - custom


See page 2 for ordering code detailed information

CROSS SECTION



MEDWDI - HLO-WAI
High Efficiency Lambertian Optic

LIGHT DISTRIBUTION



HLO-WAI - widespread asymmetric indirect optics



MEDIUS LED

WALL DIRECT/INDIRECT
ASYMMETRIC

LUMENWERX
WWW.LUMENWERX.COM

DIRECT OPTICS

High Efficiency Lambertian Optic (HLO) The High-Efficiency Lambertian Optic (HLO) shielding of diffusing 0.075" thick acrylic with up to 88% transmission and good source obscuration is combined with matte white side reflectors to create an efficient optical chamber with uniform luminosity. Luminaire brightness is controlled by the flux-to-shielding area ratio. For visual comfort, avoid high lumen output unless Medius is installed in a high ceiling application. Spacing criteria: 1.2 (longitudinal) x 1.1 (lateral).

INDIRECT OPTICS

Widespread Asymmetric Indirect Optics (WAI) The LumenWerx Widespread Asymmetric Indirect Optics (WAI) uses a vertically oriented LED array that couples light into the edge of a linear light guide. A specially designed TIR/microstructure extracts light into the desired distribution. Peak intensity hits at 110° while suppressing direct uplight. Peak-to-zenith intensity ratio is 2:1, outstanding for a compact luminaire. The Asymmetric Widespread Indirect Optic produces noticeably smoother ceiling brightness than a typical Lambertian uplight distribution.


LIGHT SOURCE - LED

Custom linear array of mid-flux LED's are cartridge-mounted with quick-connect wiring to facilitate service and thermal management. Available in 3000K, 3500K and 4000K with a minimum 80 CRI and an option for 90 CRI with elevated R9 value. Color consistency maintained to within 3 SDCM. LEDs operated at reduced drive current to optimize efficacy and lumen maintenance. All LEDs have been tested in accordance with IESNA LM-80-08 and the results have shown L80 lumen maintenance greater than 60,000 hours. Absolute product photometry is measured and presented in accordance with IESNA LM-79, unless otherwise indicated.

LUMINAIRE LENGTH

Medius is made up of standard 4, 8 and 12 foot sections that may be joined together to create longer continuous run lengths. Nominal run length must be noted in the product code. The minimum individual section available is 4 foot.

All individual sections are joined together onsite using the joiner kits provided. LumenWerx offers joiner kits that are extremely simple to work with in the field and result in a fixture that appears virtually seamless with no light leak at any connection.



joining system for Medius
Direct/Indirect

ELECTRICAL

Factory-set, adjustable output current LED driver with universal (120-277VAC) input. Dimmable from 100% to 1% with 0-10V dimming control. Rated life (90% survivorship) of 50,000 hours at 50°C max. ambient (and 70°C max. case) temperature. At maximum driver load: Efficiency > 84%, PF > 0.9, THD < 20%. Other specifiable options include Lutron Hi-Lume 1% (specify 2-wire, or Ecosystem Dim-to-Off), Lutron 5-Series (5% Ecosystem), DMX (RDM compatible) and DALI protocol drivers. All of our standard 0-10V drivers are NEMA 410 compliant.

Access: Driver is accessible for field service by removing the uplight LED and light guide cartridge

EMERGENCY

Factory installed long life high temperature recyclable Ni-Cad battery pack with test switch and charge indicator, minimum of 90 minutes operation, up to 1000 lumens per 4ft (25°C) emergency lighting output. Recharge time of 24 hours.

MOUNTING OPTIONS

Fixtures may be horizontally mounted to the wall using a bracket. For long runs, a minimum of 6" from adjacent walls is required.

FINISH

Interior - 95%, reflective matte powder coated white paint

Exterior - matte white, matte black or aluminum powder coating

Side reflector - high reflective white coating

Custom finishes are also available.

CONTROLS

LumenWerx offers several options for integrating occupancy and daylight harvesting controls in our luminaires.

STANDALONE CONTROLS

An integrated standalone sensor controls the luminaire in which it is installed. Depending on the length, more than one sensor may be necessary and may control the entire luminaire, or just a section of it. These controls operate independently. Unless otherwise agreed, location and functionality of the sensor within the luminaire are selected by LumenWerx.

Three types are available:

OMS: An integral Passive InfraRed (PIR) sensor turns luminaires on and off automatically with field-adjustable time out period. No wall control is used.

Coverage pattern for large motion has a 12' diameter with the sensor mounted 8' above the floor; for small motion, the pattern has an 8' diameter. Typically, one sensor is required for every 10' of a continuous luminaire run.

ODS: An integral, daylight harvesting sensor with closed-loop operation dims the luminaire in which it is installed in order to compensate for available daylight. The sensor measures the combination of daylight and luminaire light reflected from horizontal surfaces below the luminaire. Initial onsite calibration is required via the use of provided remote control.

OCS: Both an occupancy and a daylight sensor are installed in the luminaire.

CONNECTED CONTROLS

With Connected Controls, sensors or nodes installed in the luminaire form part of a larger control system infrastructure from manufacturers such as: Lutron*, Enlighted, Osram ENCELIUM, Acuity nLight, Crestron and others. These connected controls allow for a scalable system providing features like occupancy and daylight control, manual control, scheduling and configuration of various zones and scenes. Energy reporting and system monitoring are also possible. Specific capabilities depend on the control system being used.

LumenWerx installs the components (sensors, nodes, power packs, etc) which may be supplied to us by a third party, or procured directly by LumenWerx, depending on the control system manufacturer.

LumenWerx is solely responsible for the installation of specified components; the controls manufacturer is responsible for performance of the control system.

To indicate a LumenWerx luminaire with Connected Controls, identify the specific onsite control system to be integrated into the luminaires using the ordering code. Due to the diversity of components, you must contact controls@lumenwerx.com to assure complete compatibility with intended control system and to fully specify the luminaire.

Complete control specifications, sensor/node/power pack layout, and narrative for the control system are required for LumenWerx to create shop drawings and submittals.

* Lumenwerx offers a Lutron Vive-Enabled fixture option using either the DFCSJ-OEM-OCC (OCS Option) or DFCSJ-OEM-RF (wireless only, no sensor) Integral Fixture Modules and a DALI or EcoSystem LED driver based on customer dimming requirements.

Please contact our controls department at controls@lumenwerx.com for further assistance.

CONSTRUCTION

Housing - Extruded aluminum 0.085" nominal, matte white or aluminum powder coating. Custom finishes are also available.

End cap - Die cast Aluminum (0.95" nominal)

Joiners - Die cast Aluminum (0.95" nominal)

Interior brackets - Die formed cold rolled sheet steel 20 gauge thick

Reflectors - High reflective white coated bent aluminum

Light guide - Clear PMMA Laminated with microstructure film formed into optical TIR/extraction form

WEIGHT

Medius 4 ft - 10.5 lbs, 4.8kg

Medius 8 ft - 19.7 lbs, 8.9kg

Medius 12 ft - 28.8 lbs, 13.1kg

CERTIFICATIONS

ETL - Rated for Indoor Dry/Damp locations.

Conforms to UL Standard 1598 and certified to CAN/CSA Standard C22.2 No. 250.0.

WARRANTY

LumenWerx provides a five-year limited warranty of electrical and mechanical performance of the luminaires, including the LED boards, drivers, and auxiliary electronics. LumenWerx will repair or replace defective luminaires or components at our discretion, provided they have been installed and operated in accordance with our specifications. Other limitations apply, please refer to the full warranty on our website.